



Specification Chart

The Quick Specifications Chart is designed to allow you to compare our injectors and their capabilities at a glance.

Model	Maximum	Flow	Pressure	Ratios	Percent
D07RE5 - 3 GPM	3 GPM / 12 LPM	0.02 to 3 GPM (0.08 to 12 LPM)	4.3 to 85 PSI	1:128 to 1:18	0.8 to 5.5%
D07RE125 - 3 GPM	3 GPM / 12 LPM	0.02 to 3 GPM (0.08 to 12 LPM)	4.3 to 85 PSI	1:667 to 1:80	0.15 to 1.25%
D128R - 7 GPM	7 GPM / 27 LPM	0.09 to 7 GPM (0.34 to 27 LPM)	7 to 70 PSI	1:200/1:128/1:100	0.5/0.8/1%
D25RE10 - 8.8 GPM	8.8 GPM / 33.3 LPM	0.05 to 8.8 GPM (0.19 to 33.3 LPM)	4.3 to 57 PSI	1:33 to 1:10	3 to 10%
D14MZ520 - 9 GPM	9 GPM/34 LPM	0.05 to 9 GPM (0.19 to 34 LPM)	7 to 57 PSI	1:20 to 1:5	5 to 20%
D25F - 11 GPM	11 GPM / 42 LPM	0.05 to 11 GPM (0.19 to 42 LPM)	4.3 to 85 PSI	1:128 Fixed	0.8%
D25F1 - 11 GPM	11 GPM / 42 LPM	0.05 to 11 GPM (0.19 to 42 LPM)	4.3 to 85 PSI	1:100 Fixed	1%
D25RE2 - 11 GPM	11 GPM / 42 LPM	0.05 to 11 GPM (0.19 to 42 LPM)	4.3 to 85 PSI	1:500 to 1:50	0.2 to 2%
D25RE5 - 11 GPM	11 GPM / 42 LPM	0.05 to 11 GPM (0.19 to 42 LPM)	4.3 to 85 PSI	1:100 to 1:20	1 to 5%
D25RE09 - 11 GPM	11 GPM / 42 LPM	0.05 to 11 GPM (0.19 to 42 LPM)	4.3 to 85 PSI	1:1000 to 1:112	0.1 to 0.9%
D25RE09VFBPHY - 11 GPM	11 GPM / 42 LPM	0.05 to 11 GPM (0.19 to 42 LPM)	4.3 to 85 PSI	1:1000 to 1:112	0.1 to 0.9%
DM11F - 11 GPM	11 GPM / 42 LPM	0.02 to 11 GPM (0.08 to 42 LPM)	1.5 to 85 PSI	1:128 Fixed	0.8%
DM11RE3 - 11 GPM	11 GPM / 42 LPM	0.02 to 11 GPM (0.08 to 42 LPM)	2.2 to 57 PSI	1:128 to 1:32	0.8% to 3%
D14MZ2 - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:500 to 1:50	0.2 to 2%
D14MZ2-D - 14 GPM (Vehicle Wash)	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:500 to 1:50	0.2 to 2%
D14MZ5 - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:200 to 1:20	0.5 to 5%
D14MZ5-D - 14 GPM (Vehicle Wash)	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:200 to 1:20	0.5 to 5%
D14MZ10 - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	7 to 85 PSI	1:100 to 1:10	1 to 10%
D14MZ10-D - 14 GPM (Vehicle Wash)	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	7 to 85 PSI	1:100 to 1:10	1 to 10%
D14MZ3000 - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:3000 to 1:333	0.03 to 0.3%
D14MZ3000-D - 14 GPM (Vehicle Wash)	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:3000 to 1:333	0.03 to 0.3%
D14WL2NAF - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:500 to 1:50	0.2 to 2%

Model	Maximum	Flow	Pressure	Ratios	Percent
D14WL3000NAF - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:3000 to 1:333	0.03 to 0.3%
D14WL3000NIEAF - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:3000 to 1:333	0.03 to 0.3%
D14MZ2VFBPHY - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:500 to 1:50	0.2 to 2%
D14MZ10VFBPHY - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	7 to 85 PSI	1:100 to 1:10	1 to 10%
D14MZ3000VFBPHY - 14 GPM	14 GPM / 50 LPM	0.05 to 14 GPM (0.19 to 50 LPM)	4.3 to 85 PSI	1:3000 to 1:333	0.03 to 0.3%
D45RE3 - 20 GPM	20 GPM / 76 LPM	0.4 to 20 GPM (1.51 to 76 LPM)	7 to 70 PSI	1:200 to 1:33	0.5 to 3%
D45RE8 - 20 GPM	20 GPM / 76 LPM	0.4 to 20 GPM (1.51 to 76 LPM)	7 to 70 PSI	1:33 to 1:12	3 to 8%
D45RE15 - 20 GPM	20 GPM / 76 LPM	0.4 to 20 GPM (1.51 to 76 LPM)	7 to 70 PSI	1:500 to 1:66	0.2 to 1.5%
D8RE2 - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	2.2 to 116 PSI	1:500 to 1:50	0.2 to 2%
D8RE5 - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	2.2 to 116 PSI	1:100 to 1:20	1 to 5%
D8RE3000 - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	2.2 to 116 PSI	1:3000 to 1:800	0.03 to 0.125%
D8RE2VFBPHY - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	2.2 to 116 PSI	1:500 to 1:50	0.2 to 2%
D8RE5VFBPHY - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	2.2 to 116 PSI	1:100 to 1:20	1 to 5%
D8RE3000VFBPHY - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	2.2 to 116 PSI	1:3000 to 1:800	0.03 to 0.125%
D20S - 100 GPM	100 GPM / 379 LPM	5 to 100 GPM (18.9 to 379 LPM)	2 to 120 PSI	1:500 to 1:50	0.2 to 2%
D40WL3000NAF - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	2.2 to 116 PSI	1:3000 to 1:800	0.03 to 0.125%
D40WL3000NIEAF - 40 GPM	40 GPM / 151 LPM	2.2 to 40 GPM (8.32 to 151 LPM)	5 to 116 PSI	1:3000 to 1:800	0.03 to 0.125%
D132MZ1 - 132 GPM	132 GPM / 500 LPM	35.2 to 132 GPM (133 to 500 LPM)	7 to 87 PSI	1:1000 to 1:100	0.1 to 1%
D132WL5000 - 132 GPM	132 GPM / 500 LPM	35.2 to 132 GPM (133 to 500 LPM)	7 to 87 PSI	1:5000 to 1:500	0.02 to 0.2%
D132WL30000 - 132 GPM	132 GPM / 500 LPM	35.2 to 132 GPM (133 to 500 LPM)	7 to 87 PSI	1:30000 to 1:3000	0.003 to 0.03%
D400MZ02 - 400 GPM	400 GPM / 1514 LPM	110 to 400 GPM (416 to 1514 LPM)	7.25 to 116 PSI	1:5000 to 1:500	0.02 to 0.2%
D400MZ05 - 400 GPM	400 GPM / 1514 LPM	110 to 400 GPM (416 to 1514 LPM)	7.25 to 116 PSI	1:1000 to 1:200	0.1 to 0.5%
D400MZ30000 - 400 GPM	400 GPM / 1514 LPM	110 to 400 GPM (416 to 1514 LPM)	7.25 to 116 PSI	1:30000 to 1:8000	0.003 to 0.0125%



2090 Sunnydale Blvd. • Clearwater, FL 33765
1-800-523-8499 • www.dosatronusa.com

Updated 10/30/19