



# DOSATRON®

WATER POWERED DOSING TECHNOLOGY

# Mobile Coolant Fill System

## Easily fill machine cells with fresh coolant throughout your shop!

The Mobile Coolant Fill System conveniently allows the user to add and adjust coolant concentrations on demand.

- Simply fill the onboard 25-gallon tank with concentrate
- Connect a garden hose, water supply to the Dosatron
- Set the Dosatron to the desired concentration
- Squeeze the gas nozzle style valve and add the coolant/water solution directly to the machine sump

Dosatron's New Mobile Coolant Fill System includes a durable, roto-molded 25-gallon coolant concentrate tank, featuring an onboard Dosatron water-powered metering pump, a simple garden hose water connection swivel, "no flat" tires, and an EZ fill, gas nozzle style valve, with fill hose.

**Dosatron metering pumps are also great for:**

- Vibratory Compounds
- Die Lubes
- Detergents / Cleaners
- Rust Inhibitors



### 25-Gallon System Features:

- 25-gallon rugged tank
- 4 wheels for stability
- No tilt ergonomic design
- Easy to maneuver
- Refractometer storage compartment
- Stainless steel brackets
- 10' delivery hose
- Gasoline style gun for easy fill
- Integrated dosing pump (Dosatron D14MZ5 or D14MZ10)
- Easy plumbing hookup



### Hook-Up Kit Features:

- Elbows
- Unions
- Nipples
- Hose
- Clamps
- Strap
- 10' delivery hose
- Gasoline style gun

Dosatron metering pump, hook-up kit and 25-gallon cart, all sold separately.

**For more information call 1-800-523-8499 • 1-727-443-5404  
or visit [www.dosatronusa.com](http://www.dosatronusa.com)**

## METERING PUMP SPECIFICATIONS

D14 Chemical Metering Pumps			
MODEL		D14MZ5	D14MZ10
DILUTION RANGE		1:200 to 1:20	1:100 to 1:10
FLOW RANGE		0.05 GPM - 14 GPM	0.05 GPM - 14 GPM
INJECTION PERCENTS		0.5% to 5%	1% to 10%
PRESSURE RANGE		4.3 to 85 PSI	7 to 85 PSI
CONNECTIONS		3/4" NPT	3/4" NPT
RECOMMENDED ACCESSORY KIT		IPK34 - 14 GPM	IPK34 - 14 GPM

All units include: mounting bracket, suction hose, weighted strainer, and quick start guide.  
Please review the basic installation drawing for recommended accessories.  
MAXIMUM TEMPERATURE: 104 °F

## PRE-PLUMBED SYSTEMS

Call 1-800-523-8499 to order your pre-plumbed panels and locking cabinets.



Stamping Compound System



Vibratory Compound System



Coolant Mixing System

## Dosa Lock



Control your chemical costs by securing your settings with the tamper resistant Dosa Lock!

Made out of high impact strength polypropylene that is resistant to most chemicals and includes lock and key.

Fits pumps ranging from 11 GPM up to 40 GPM.

## Customer Service

At Dosatron, we stand behind our units. Our world-class customer service team is always ready to assist you with service and support, for as long as you own your Dosatron.

## Not sure what unit fits your needs?



It's easy to CHAT at [www.dosatronusa.com](http://www.dosatronusa.com). Just enter your question and we will be glad to assist.

**Want an easy preventive maintenance reminder?** Sign up at [www.dosatronusa.com/pm](http://www.dosatronusa.com/pm) for Dosatron's Preventive Maintenance Program.

## Ready to order?

Call 1-800-523-8499 for a distributor near you.



**DOSATRON®**

2090 Sunnydale Blvd.  
Clearwater, FL 33765 USA  
1-727-443-5404  
(Fax) 727-447-0591

**1-800-523-8499**  
[www.dosatronusa.com](http://www.dosatronusa.com)

