



DOSATRON®

WATER POWERED DOSING TECHNOLOGY

14 GPM: D14MZ5

PRODUCT DESCRIPTION

The versatile Dosatron **D14MZ5-14 GPM** is used in industries such as metal processing, food safety & sanitation, carwash, and printing. Is simple to install with the Industrial Plumbing Kit (IPK34-14GPM) and is easy to maintain.

PRODUCT SPECIFICATIONS

| | |
|------------------------------|---|
| Dilution Range: | 1:200 to 1:20 (0.5% to 2%) |
| Water Flow Range: | 0.05 to 14 GPM |
| Operating Pressure Range: | 4.3 to 85 PSI |
| Available Housing Materials: | <ul style="list-style-type: none"> • Polypropylene (Standard Blue) • PVDF (White) |
| Other Options: | Viscous |
| Dimensions: | 19 1/18" x 6 5/16" |
| Weight: | 6 lbs |
| Connection Size: | 3/4" NPT |
| Maximum Temperature: | 104° F |
| Included Accessories: | 6' clear suction tube, strainer, weight, mounting bracket and operating manual |
| Recommended Accessories: | pressure regulator, 200 mesh filter, check valve |



MAINTENANCE KITS

Injection Seal Kit (Part #: **PJDI120**) - For yearly maintenance

Injection Seal Kit for Viscous (Part #: **PJDI120V**) - For yearly maintenance

Rebuild Kit (Part #: **MKD14MZ5**) - Extends the life of your unit

Call 800-523-8499 to order the Dosatron for your specific application



DOSATRON®

WATER POWERED DOSING TECHNOLOGY

14 GPM: D14MZ5

Recommended Installation for Industrial Applications

IPK34 - 14 GPM Industrial Plumbing Kit



- 3/4" polypropylene single union ball valve
- 1/2" stainless steel ball valve
- 3/4" poly 200 mesh tee filter
- 3/4" brass pressure regulator w/gauge
- 3/4" 14 GPM flow restrictor
- 3/4" polypropylene check valve
- 3/4" union schedule 80 PVC
- 3/4" x 2" polypropylene fittings
- 1/2" x 2" polypropylene fittings
- 1/2" x 1/2" barb fitting
- 3/4" male to 1/2" female reducer bushing
- 3/4" Tee
- 3/4" street elbows
- Roll of Teflon tape
- Instruction card
- Zip tie

Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatronusa.com